

**1. PRODUCT AND COMPANY IDENTIFICATION**

<b>Product Code</b>	SKT122A
<b>Product Name</b>	Sikatop 122 Part A
<b>Product Description</b>	2-component polymer modified cementitious repair mortar.
<b>Manufacturer/Supplier</b>	Sika Limited Watchmead Welwyn Garden City Hertfordshire. AL7 1BQ tel. 01707 394444 Fax. 01707 329129

**2. COMPOSITION/INFORMATION ON THE COMPONENTS****Preparation - Hazardous ingredients ( Europe )**

<b>Component</b>	<b>CAS/EINECS</b>	<b>Concentration</b>	<b>Classification</b>	<b>Risk Phrases</b>
Alkyl phenol ether sulphate		0.10% - 1.00%	Xi, N	R41, R51/53

**3. HAZARD IDENTIFICATION**

**Main Hazards** Not classified as hazardous.

**4. FIRST AID MEASURES**

<b>Eye Contact</b>	Immediately flood the eye with plenty of water for at least 15 minutes, holding the eye open. Eyelids should be held away from the eyeball to ensure thorough rinsing. Obtain medical attention if soreness or redness persists.
<b>Skin Contact</b>	Wash skin thoroughly with soap and water. If material proves difficult to remove, use suitable skin cleanser (not solvent). Contaminated clothing should be washed or dry-cleaned before re-use.
<b>Ingestion</b>	Wash out mouth with water. If vomiting occurs naturally, rinse mouth and repeat administration of water. Obtain medical attention.
<b>Inhalation</b>	Remove from exposure. Provide symptomatic medical treatment if required.

**5. FIRE FIGHTING MEASURES**

<b>Extinguishing Media</b>	Use DRY chemicals, CO2, alcohol foam or water spray.
<b>Special Hazards of Product</b>	Combustion will produce smoke, carbon dioxide and carbon monoxide.
<b>Protective Equipment for Fire-Fighting</b>	Wear self contained breathing apparatus.



# SAFETY DATA SHEET

## Sikatop 122 Part A

Date of issue - 22/12/2005.

SKT122A

### 6. ACCIDENTAL RELEASE MEASURES

<i>Personal Precautions</i>	Wear appropriate protective clothing.
<i>Environmental Precautions and Clean-up Methods</i>	Prevent the material from entering drains or water courses.
<i>Spillages</i>	Contain and absorb using earth, sand or other inert material. Transfer into suitable containers for recovery or disposal.

### 7. HANDLING AND STORAGE

<i>Handling</i>	Use in well ventilated area. Avoid contact with eyes, skin and clothing. Keep container tightly closed when not in use.
<i>Storage</i>	Storage area should be: cool. dry. Store in original containers. Protect from extremes of cold. Storage temperature should be controlled to between 5 and 25 °C.

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

<i>Engineering Control Measures</i>	Use of the basic principles of Industrial Hygiene will enable this material to be used safely.
<i>Respiratory Protection</i>	Respiratory protection not normally required.
<i>Hand Protection</i>	Wear suitable impervious gloves. ( Nitrile. PVC. rubber )
<i>Eye Protection</i>	Wear safety glasses if risks of accidental contamination are possible during application.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

<i>Physical State</i>	Liquid.
<i>Color</i>	Milky-white.
<i>Odor</i>	Characteristic.
<i>pH</i>	7.5 (typical)
<i>Boiling Point °C</i>	100
<i>Flash Point °C</i>	Not applicable.
<i>Solubility - Water</i>	Miscible in water.
<i>Density (kg/m3)</i>	Approx. 1020 at 20 °C.
<i>Viscosity (at 20°C)</i>	Less than 200 at 20 °C. (measured as mPa.s)

### 10. STABILITY AND REACTIVITY

<i>Stability</i>	Stable under normal conditions.
<i>Conditions to avoid</i>	Protect from frost
<i>Materials to avoid</i>	None under normal conditions.
<i>Hazardous Decomposition Products</i>	After evaporation of water, combustion will generate: oxides of carbon. acrylic monomers, acrid smoke and irritating fumes.



# SAFETY DATA SHEET

## Sikatop 122 Part A

Date of issue - 22/12/2005.

SKT122A

### 11. TOXICOLOGICAL INFORMATION

<i>Acute toxicity</i>	Low order of acute toxicity.
<i>Eye irritation</i>	May cause slight transient irritation.
<i>Skin irritation</i>	Frequent or prolonged skin contact may cause some local short term skin irritation.

### 12. ECOLOGICAL INFORMATION

<i>Mobility</i>	Mobile liquid. Emulsifiable in water.
<i>Persistence/degradability</i>	The product is expected to be readily biodegradable.
<i>Ecotoxicity</i>	Maybe harmful to aquatic species

### 13. DISPOSAL

<i>Product Disposal</i>	Arrange for disposal via a licensed waste contractor.
<i>Container Disposal</i>	Dispose of containers with care. Empty packaging should be removed by a licensed waste contractor.

### 14. TRANSPORT INFORMATION

<i>ADR/RID : Proper shipping name</i>	Not Regulated under ADR/RID
<i>IMDG : Proper shipping name</i>	Not Regulated under IMDG
<i>IATA : Proper shipping name</i>	Not Regulated under ICAO

### 15. REGULATORY INFORMATION

<i>Risk Phrases</i>	None assigned.
<i>Safety Phrases</i>	None assigned

### 16. OTHER INFORMATION

<i>First Issue Date</i>	14.11.1995
<i>Revisions Highlighted</i>	Composition and Information on Ingredients
<i>Uses and Restrictions</i>	Customers are urged to ensure that the product is entirely suitable for their own purpose. It is the customer's responsibility to ensure that a suitable and sufficient assessment of the risks created by the use of the product is undertaken.
<i>UK Legislation</i>	Health and Safety at Work etc Act, 1974, and relevant Statutory Provisions. SI 2002/1689: Chemicals (Hazard Information and Packaging) Regulations SI 2002/2677: The Control of Substances Hazardous to Health Regulations SI No 2839 1991 Environmental Protection (Duty of Care) Regulations.
<i>UK Guidance Publications</i>	General Approved Code of Practice to COSHH Regulations, HSE.



## SAFETY DATA SHEET

### Sikatop 122 Part A

Date of issue - 22/12/2005.

SKT122A

---

**Footnote**

The information contained in this SDS corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the Technical Data Sheet prior to use.

**1. PRODUCT AND COMPANY IDENTIFICATION**

<b>Product Code</b>	SKT122B
<b>Product Name</b>	Sikatop 122 Part B
<b>Product Description</b>	2-component polymer modified cementitious repair mortar.
<b>Manufacturer/Supplier</b>	Sika Limited Watchmead Welwyn Garden City Hertfordshire. AL7 1BQ tel. 01707 394444 Fax. 01707 329129

**2. COMPOSITION/INFORMATION ON THE COMPONENTS****Preparation - Hazardous ingredients ( Europe )**

<b>Component</b>	<b>CAS/EINECS</b>	<b>Concentration</b>	<b>Classification</b>	<b>Risk Phrases</b>
Portland Cement	65997-15-1	25.00% - 50.00%	Xi	R41
Pulverised fuel ash	68131-74-8	2.50% - 10.00%	-	-
Silica,amorphous	69012-64-2	1.00% - 2.50%	-	-

**3. HAZARD IDENTIFICATION**

**Main Hazards** Risk of serious damage to eyes.

Dry cement powders in normal use have no harmful effect on the dry skin However when cement is mixed with water or becomes damp,alkalies are released which can be harmful.  
Contact with wet cement or wet mortar may cause irritation,dermatitis or burns.

**4. FIRST AID MEASURES**

**Eye Contact** Immediately flood the eye with plenty of water for at least 15 minutes, holding the eye open.  
Obtain medical attention urgently.

**Skin Contact** Wash skin thoroughly with soap and water.  
Obtain medical attention if blistering occurs or redness persists.  
Contaminated clothing should be washed or dry-cleaned before re-use.

**Ingestion** Do not induce vomiting. Wash out mouth with water.

**Inhalation** Remove from exposure.  
In cases of possible respiratory irritation or if feeling unwell in cases of prolonged exposure,obtain medical attention.

**5. FIRE FIGHTING MEASURES**

**Extinguishing Media** Not combustible.  
Select extinguishing agent appropriate to other materials involved.

**Special Hazards of Product** None.



# SAFETY DATA SHEET

## Sikatop 122 Part B

Date of issue - 21/12/2005.

SKT122B

### 6. ACCIDENTAL RELEASE MEASURES

<i>Personal Precautions</i>	Wear appropriate protective clothing.
<i>Environmental Precautions and Clean-up Methods</i>	Prevent the material from entering drains or water courses.
<i>Spillages</i>	Avoid creating a dust. Sweep up into suitable containers for recovery or disposal.

### 7. HANDLING AND STORAGE

<i>Handling</i>	Avoid inhaling dust. Exposure by inhalation or skin contact should be minimised by good Industrial Hygiene practices.
<i>Storage</i>	Use in well ventilated area. Storage area should be: cool. dry.

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Occupational Exposure Limits - GB

Portland Cement	UK EH40: WEL 10mg/m <sup>3</sup> 8h TWA. Dust, total inhalable:
	UK EH40: WEL 4mg/m <sup>3</sup> 8h TWA. Dust, respirable:
Pulverised fuel ash	UK EH40: WEL 10 mg/m <sup>3</sup> 8h TWA. Dust, total inhalable:
	UK EH40: WEL 4 mg/m <sup>3</sup> 8h TWA. Dust, respirable:
Silica, amorphous	UK EH40: WEL 6 mg/m <sup>3</sup> 8h TWA. Dust, total inhalable:
	UK EH40: WEL 2.4 mg/m <sup>3</sup> 8h TWA. Dust, respirable:

<i>Engineering Control Measures</i>	Use of the basic principles of Industrial Hygiene will enable this material to be used safely. Every effort should be made to prevent airborne dusts arising during mixing operations.
<i>Respiratory Protection</i>	If limits are exceeded use an approved dust mask.
<i>Hand Protection</i>	Wear suitable impervious gloves.
<i>Eye Protection</i>	Dust tight goggles.
<i>Body Protection</i>	Protective clothing should be worn which ensures that cementitious materials do not come into contact with the skin. Particular care should be taken to ensure that wet mortar does not enter boots/footwear.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

<i>Physical State</i>	Powder.
<i>Color</i>	Grey.
<i>Odor</i>	None.
<i>pH</i>	Approx. 12 in water.
<i>Flash Point °C</i>	Not applicable.
<i>Solubility - Water</i>	Partially soluble.
<i>Density (kg/m<sup>3</sup>)</i>	Approx. 1250. (loose)

### 10. STABILITY AND REACTIVITY

<i>Stability</i>	Stable under normal conditions.
<i>Materials to avoid</i>	Strong mineral acids.
<i>Hazardous Decomposition Products</i>	None known.



# SAFETY DATA SHEET

## Sikatop 122 Part B

Date of issue - 21/12/2005.

SKT122B

### 11. TOXICOLOGICAL INFORMATION

<i>Acute toxicity</i>	Low order of acute toxicity.
<i>Eye irritation</i>	Cement is a severe eye irritant. Gross exposures or untreated mild exposures can lead to chemical burning and ulceration of the eye.
<i>Skin irritation</i>	Cement and/or water/cement mixtures may cause irritant contact dermatitis, allergic dermatitis, and/or burns.

### 12. ECOLOGICAL INFORMATION

<i>Mobility</i>	The product is sparingly soluble in water.
<i>Persistence/degradability</i>	Inorganic basis, therefore non biodegradable.
<i>Ecotoxicity</i>	The alkalinity of this product will have a local effect on ecosystems sensitive to changes in pH


### 13. DISPOSAL

<i>Product Disposal</i>	As an inert material it may be disposed of via an approved solid waste disposal facility.
<i>Container Disposal</i>	Empty packaging may be disposed along with normal builders waste via an authorised waste contractor.

### 14. TRANSPORT INFORMATION

<i>ADR/RID : Proper shipping name</i>	Not Regulated under ADR/RID
<i>IMDG : Proper shipping name</i>	Not Regulated under IMDG
<i>IATA : Proper shipping name</i>	Not Regulated under ICAO

### 15. REGULATORY INFORMATION

<i>Label Requirements</i>	Irritant 
<i>Risk Phrases</i>	Risk of serious damage to eyes.
<i>Safety Phrases</i>	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. After contact with skin, wash immediately with plenty of soap and water Wear eye/face protection.

### 16. OTHER INFORMATION

<i>First Issue Date</i>	14.11.1995
<i>Revisions Highlighted</i>	Composition / information on ingredients Exposure Controls and Personal Protection Toxicological Information Regulatory Information
<i>Uses and Restrictions</i>	Customers are urged to ensure that the product is entirely suitable for their own purpose. It is the customer's responsibility to ensure that a suitable and sufficient assessment of the risks created by the use of the product is undertaken.



## SAFETY DATA SHEET

### Sikatop 122 Part B

Date of issue - 21/12/2005.

SKT122B

---

#### *UK Legislation*

Health and Safety at Work etc Act, 1974, and relevant Statutory Provisions.

SI 2002/1689: Chemicals (Hazard Information and Packaging) Regulations

SI 2002/2677: The Control of Substances Hazardous to Health Regulations

SI No 2839 1991 Environmental Protection (Duty of Care) Regulations.

#### *UK Guidance Publications*

General Approved Code of Practice to COSHH Regulations, HSE.

EH40, Occupational Exposure Limits, HSE. Revised Annually.

EH44, Dust in the Workplace: General Principles of Protection, HSE.

EH26, Occupational Skin Diseases: Health and Safety Precautions, HSE.

CONIAC Health Hazard Information Sheet No.26 (Cement)

#### *Footnote*

The information contained in this SDS corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the Technical Data Sheet prior to use.