Page 1/6



Material Safety Data Sheet according to 1907/2006/EC, Article 31

Printing date 02.02.2009 Revision: 02.02.2009

1 Identification of substance

· Product details

Trade name Waterproofing Filler

· Article number: 0426

· Application of the substance / the preparation Anti-moisture agent

· Manufacturer/Supplier: Remmers Baustofftechnik Produktions-GmbH Bernhard-Remmers-Str. Gewerbegebiet Süd-Ost 04849 Bad Düben

Tel.: 034243/306-0 Fax: 034243/30699

Informing department:

Product Safety department: Tel.: +49 (0)5432/83-138/-538

E-Mail: sales@remmers.co.uk

Emergency information:

during working hours:

U.K.: Tel.: +44 (0) 845 373 0103 Far East: Tel.: +65(0)67410277 Head Office Germany: Tel.: +49 (0)5432 83 185 after working hours: Tel.: +49 (0)171/6428-297

2 Hazards identification

· Hazard designation:



Xi Irritant

- · Information pertaining to particular dangers for man and environment R 36/38 Irritating to eyes and skin.
- **Classification system**

The classification is in line with current EC lists. It is expanded, however, by information from technical literature and by information furnished by supplier companies.

The danger designation "irritating" does not apply to the dry powder but rather only after moisture or water has been admitted (alkaline reaction).

Additional information: low chromate content according to directive 2003/53 EG

3 Composition/information on ingredients

- · Chemical characterization
- · Description: Inorganic binder combination with fillers and additives and organic additives

· Dangerous components:				
CAS: 65997-15-1	Cement	Xi; R 36/38-43	10-20%	
EINECS: 266-043-4				
CAS: 7631-86-9	silicon dioxide, chemically prepared		1-2.5%	
EINECS: 231-545-4	• • •			
(Contd. on page			on page 2)	

(Contd. on page

Printing date 02.02.2009 Revision: 02.02.2009

Trade name Waterproofing Filler

		(Conto	d. of page 1)
CAS: 554-13-2	lithium carbonate	Xn; R 22	1-2.5%
EINECS: 209-062-5			
CAS: 14808-60-7	Quartz (SiO2)		60-80%
EINECS: 238-878-4			

[·] Additional information For the wording of the listed risk phrases refer to section 16.

4 First aid measures

After inhalation

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness bring patient into stable side position for transport.

After skin contact

Wash immediately with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eye contact

Rinse opened eye for several minutes under running water.

Seek medical treatment.

- · After swallowing Call a doctor immediately.
- · Information for doctor see item 3

5 Fire fighting measures

- · Suitable extinguishing agents Use fire fighting measures that suit the environment.
- · Protective equipment: No special measures required.

6 Accidental release measures

· Person-related safety precautions:

Avoid causing dust.

Avoid skin contact. Avoid eye contact.

· Measures for environmental protection:

Avoid uncontrolled admittance of water. Avoid uncontrolled runoff after admittance of water. Avoid runoff into sewage system and receiving water.

Measures for cleaning/collecting:

Collect mechanically.

Keep away from water.

· Additional information:

Hardens after contact with water. After hardening it can be disposed of as concrete (European waste catalogue: EWC-Code: 170101).

7 Handling and storage

- Handling
- Information for safe handling:

Avoid the formation of dust.

Protect against moisture. Keep out of reach of children. Avoid skin contact. Avoid eye contact.

- Information about protection against explosions and fires: The product is not flammable
- Storage
- Requirements to be met by storerooms and containers:

Store in closed rooms protected against moisture. Extraction of dust in compliance with BImSchG or Technical Instructions Air.

· Information on storage in a common storage facility: none

(Contd. on page 3)

Printing date 02.02.2009 Revision: 02.02.2009

Trade name Waterproofing Filler

(Contd. of page 2)

· Further information about storage conditions:

Keep container tightly closed.

Store dry.

Protect from humidity and keep away from water.

8 Exposure controls and personal protection

· Additional information about design of technical systems: No further data; see item 7.

· Components with limit values that require monitoring at the workplace:

65997-15-1 Cement

WEL Long-term value: 10* 4** mg/m³ *inhalable dust **respirable dust

- · Additional information: The lists that were valid during compilation were used as a basis.
- · Personal protective equipment
- · General protective and hygienic measures

Keep away from food, beverages and animal feed.

Do not eat, drink or smoke while working.

Immediately remove soiled, saturated clothing.

Use skin protection cream for preventive skin protection.

Wash hands before pauses and after work.

Avoid contact with eyes and skin.

Do not inhale dust / smoke / mist.

Observe Professional Association regulations.

· Respiratory equipment:

Short term filter device:

Filter P2.

Code of Practice ZH 1 / 701 Hauptverband der Gewerbl. BG

· Protection of hands:

Protective gloves.

Avoid contact with skin. Wear suitable protective gloves.

- · Material of gloves Nitrile rubber, NBR
- · Penetration time of glove material

Break through time: max. 240 min (DIN EN 374).

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:

Tightly sealed safety glasses.

Code of Practice BGR 192 Hauptverband der Gewerbl. BG: Avoid contact with eyes. In case of eye contact, rinse immediately and thoroughly with water. Seek medical advice.

· Body protection: Protective work clothing.

9 Physical and chemical properties:

· General Information

Form: Powder Grey Odour: Odourless

Change in condition

Melting point/Melting range: > 1000°C Boiling point/Boiling range: Not determined

· Flash point: Not applicable

(Contd. on page 4)

Printing date 02.02.2009 Revision: 02.02.2009

Trade name Waterproofing Filler

		(Contd. of page 3)
· Self-inflammability:	Product is not self-igniting.	
· Danger of explosion:	Product is not explosive.	
· Density		
· Bulk apparent density at 20	° C ca. 1.5 kg/dm3	
· Solubility in / Miscibility wit Water:	t h miscible at 1:5	
· pH-value (10 g/l) at 20°C:	ca. 12	

10 Stability and reactivity

· Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

No decomposition if handled and stored according to specifications.

Avoid the entrance of moisture

- · Dangerous reactions No dangerous reactions known
- Dangerous decomposition products:

None if used properly.

None if stored properly.

11 Toxicological information

- · Acute toxicity:
- · Primary irritant effect:
- · on the skin: Irritates skin and mucous membranes.
- · on the eye: Irritating effect.
- · Experience with humans:

If the information in items 6 and 8 is observed, no special dangers according to the following risk phrase(s) are known:

R 36/38

12 Ecological information:

· Ecotoxical effects:

Only possible in case of unintentional release of larger amounts in connection with water through increased pH value.

General notes:

Water hazard class 1 : slightly hazardous to water.

Do not allow product to reach ground water, bodies of water or sewage system.

according to appendix 4 VwVwS

13 Notes on disposal:

- · Product:
- · Recommendation

The given refuse codes are recommendations based upon the intended use of the product. Because of special use and disposal conditions at the user's, other codes may apply under other conditions. May be used again if taken up in dry. After the addition of water and subsequent hardening, dispose of as concrete.

(Contd. on page 5)

Printing date 02.02.2009 Revision: 02.02.2009

Trade name Waterproofing Filler

(Contd. of page 4)

• European waste catalogue

17 00 00 | CONSTRUCTION AND DEMOLITION WASTES (INCLUDING EXCAVATED SOIL FROM

CONTAMINATED SITES)

17 01 00 concrete, bricks, tiles and ceramics

17 01 01 concrete

· Uncleaned packaging:

· Recommendation: Disposal must be made according to official regulations.

14 Transport information

- · Land transport ADR/RID and GGVS/GGVE (cross-border/domestic)
- ADR/RID-GGVS/E Class: -
- · Maritime transport IMDG/GGVSea:
- IMDG/GGVSea Class:
- · Air transport ICAO-TI and IATA-DGR:
- ICAO/IATA Class:
- Transport/Additional information: Not a hazardous good according to the above regulations.

15 Regulatory information

Designation according to EC guidelines:

The product has been classified and labelled in accordance with EC Guidelines / Ordinance on Hazardous Materials (GefStoffV)

Code letter and hazard designation of product:



Xi Irritant

· Risk phrases:

36/38 Irritating to eyes and skin.

- Safety phrases:
- 2 Keep out of the reach of children.
- 22 Do not breathe dust.
- 24/25 Avoid contact with skin and eyes.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- 37 Wear suitable gloves.
- · Special labelling of certain preparations: low chromate content according to directive 2003/53 EG
- Product Code: ZP 1
- · National regulations
- · Water hazard class:

Water hazard class 1: slightly hazardous to water. according to appendix 4 VwVwS

Other regulations, limitations and prohibition ordinances

Corrosive properties are set free when worked with water; therefore experience is expected of the user and our notes on working are to be observed.

Professional Association Principles/Industrial Medicine regulations, e.g. principles of industrial medicine Occupational Safety Regulations (VBG, ZH-1/Codes of Practice, etc.).

GB

Printing date 02.02.2009 Revision: 02.02.2009

Trade name Waterproofing Filler

(Contd. of page 5)

16 Other information:

This data is based on our present state of knowledge. However, it does not constitute a guarantee for any specific product features and does not establish a legally valid contractual relationship. Delivery specifications are found in the respective Technical Information Sheets.

- · Relevant R-phrases
- 22 Harmful if swallowed.
- 36/38 Irritating to eyes and skin.
- 43 May cause sensitisation by skin contact.
- · Department issuing data specification sheet: Product Safety department

0.0